


2 digit and smile face 2 color radar speed sign



IP54



ISO





2 digit and smile face 2 color radar speed sign uses the principle of radar speed measurement, combined with LED technology, to display the speed of the vehicle to the driver in time. Generally speaking, the speed feedback sign consists of three parts: 1) Speed limit sign; 2) Radar speed measuring device; 3) Electronic display board; The display board will show the speed of the vehicle, and if there are multiple vehicles driving in the area at the same time, the electronic display board will show the speed of the fastest vehicle among these vehicles.

2 digit and smile face 2 color radar speed sign is the solution that fits your budget. This compact radar speed sign offers exceptional visibility and power efficiency in a lightweight and portable solution. Featuring the options you need at remarkably affordable pricing, the LPRS driver feedback sign will help you keep your neighborhoods safe for years to come.

2 digit and smile face 2 color Radar Speed Sign feedback sign is a device equipped with a speed limit sign and can display the speed of passing vehicles in the detection area on the LED screen in real-time. The vehicle speed feedback sign is widely used in the subsequent radar speed measurement.

2 digit and smile face 2 color Radar Speed Sign displays the speed of the vehicle on the LED screen through radar speed measurement. The advanced speed feedback sign can also display the green speed value for average speed, and the read speed value for Overspeed to warn the driver. Drivers pay attention to controlling their speed. Surveys have shown that vehicle feedback signs can be effective in reducing vehicle speed.

The power supply mode of the vehicle speed feedback sign can be a 220V mains power supply, or it can be combined with a solar panel and battery power supply. In other remote speed-limited sections such as highways that is not convenient to use electricity, the solar power supply is efficient.

Features

The mobile phone APP to set parameters within 10 meters, and can support Apple, Android and Hongmeng operating systems.

There are ten levels of sensitivity. 1 is the highest sensitivity and 10 is the lowest sensitivity.

There are ten levels of brightness. 1 is the darkest and 10 is the brightest

Imported raw materials (including Taiwan-made) high-brightness light-emitting diodes (LEDs), higher brightness and longer life, the lamp beads are eye-catching and distinct in color, and have good visibility both during the day and at night.

Imported professional traffic radar is adopted, with high-precision vehicle real-time display function, accurate and reliable speed measurement results, strong anti-drying ability and high precision.

Radar speed limit card supports customization, which are 20, 30, 40, 50, 60... or other customized values.

2 digit and smile face 2 color radar speed sign supports a variety of power supply methods (solar, AC, current or battery). Solar power supply continuous rainy days for 7-10 working days.

radar speed speed sign is sealed and waterproof, and can adapt to all kinds of bad weather.

IP54

CE


RoHS
COMPLIANT

ISO

1
YEARS
WARRANTY

2 digit and smile face 2 color Radar Speed Sign

Size:



Applications

It is suitable for occasions requiring traffic management such as highways, airports, mines, enterprises, schools, hospitals, etc

Display parameter

Product size	1200*480*90mm
88 digital screen LED quantity	Total 234 (red and green two-in-one)
Smile face screen LED quantity	green:104 red:88
LED Brightness	red, 120° , 5050, luminous intensity (550 - 750 mcd/LED)
	Green, 120° , 5050, luminous intensity (800 - 1400 mcd/LED)
Raw material	Imported raw materials (including Taiwan-made) high-brightness light-emitting diodes (LEDs)
Light decay	10000h/3 years working time, light decay (mcd) ≤20%
3M Mode Material	3M engineering grade (yellow or white can be optional)
Front speed limit pane	20 km/30/40/50/60 (optional)
PCB material	Epoxy glass cloth laminate (FR4), using Kingboard A2 sheet, thickness ≥1.6mm
Weatherproof Rating	Weatherproof, IP54 level compliant. Non-sealed and ventilated.
Three-proof treatment	The use of silicone three-proof paint, evenly brushed on one side of the PCB circuit, can effectively prevent moisture, salt spray, anti-static, anti-mildew, and other characteristics
Visible distance	Above 300 Meters
Mounting Height	2.5 - 4m
Standard Mounting	60mm galvanised steel column
Power consumption	≤20W
Operating Temperatures	-30° to +60° C°
Certified	ISO 9001: 2015, CE
Warranty Period	1 year

IP54

CE


RoHS COMPLIANT

ISO

1 YEARS WARRANTY

2 digit and smile face 2 color Radar Speed Sign

System combination:



APP setting

Radar Direction	two-way detection or two lanes
Radar Direction	1-20 can be choose
speed unit	km/h or Mile /h can be choose
Communications	Wifi
Trigger speed	5-70(it can be setting)

Power Options

DC Power Input	12 V
Solar Panel Options	60W
Battery	3pcs*13ah lithium battery(advise you buy it in your local market
Continuous rainy days	7-10 days

Radar Specification

Working voltage	Solar powered DC12V
Radar working frequency	24.125 GHz or 24.200 GHz
Detection speed range	10-250KM/H
Detection distance	Standard 200Meters (100meters , 50meters)
Strobe	Dual Strobe and Single Strobe
Internal	SS300 Doppler
Output Power (EIRP)	20dBm
Antenna Angle	Horizontal: 30° , Pitch: 16° (3dB Beamwidth, Actual Detection Angle Greater Than 4 Lanes)
Speed measurement error	±1 to ±3 KM/H (when the angle between the direction of motion and the radar beam azimuth is 0 degrees)
Radar response time	≤50ms

IP54

CE

RoHS COMPLIANT

ISO

1 YEARS WARRANTY